

DEVELOPMENT OF A TARGET PRODUCT PROFILE FOR A POINT-OF-CARE CARDIOMETABOLIC DEVICE

Beatrice Vetter¹, David Beran², Philippa Boulle³, Arlene Chua³, Roberto de la Tour³, Lucy Hattingh⁴, Pablo Perel⁵, Gojka Roglic⁶, Rangarajan Sampath¹, Michael Woodman⁷, Sigiriya Aebischer Perone^{2,8}

¹ FIND, Geneva, Switzerland; ² Division of Tropical and Humanitarian Medicine, University of Geneva and Geneva University Hospitals, Geneva, Switzerland; ³ Médecins Sans Frontières (MSF), Geneva, Switzerland; ⁴ LH Consulting, Berkeley, California, USA; ⁵ Centre for Global Chronic Conditions, London School of Hygiene & Tropical Medicine, UK; ⁶ Department for Noncommunicable Diseases, World Health Organization (WHO), Geneva, Switzerland; ⁷ United Nations High Commissioner for Refugees (UNHCR), Geneva, Switzerland; ⁸ International Committee of the Red Cross (ICRC), Geneva, Switzerland

Corresponding author: Beatrice N. Vetter, FIND, 9 Chemin des Mines, 1202 Geneva, Switzerland; +41 (0) 22 710 05 90; beatrice.vetter@finddx.org

CONTENTS

Abbreviations	3	İ
Overview Introduction Methods Results Conclusion	4 4 4 4	
Background	5	
Methods Draft preparation Consensus building TPP finalization Ethics and consent	6 6 8 9 9	
Results Online survey and semi-structured interviews TPP finalization Ranking of device characteristics	10 10 13 18	
Discussion	20	•
Conclusion	21	•
References	22	•
Annex	24	•

ABBREVIATIONS

CSLI	Clinical and Laboratory Standards Institute
CVD	Cardiovascular disease
HDL	High-density lipoprotein
LDL	Low-density lipoprotein
LMIC	Low- and middle-income country
MSF	Médecins Sans Frontières
NCD	Non-communicable disease
PCR	Polymerase chain reaction
POC	Point of care
TC	Total cholesterol
ТРР	Target product profile
USD	United States dollars
WHO	World Health Organization

OVERVIEW

Introduction:

Multi-parameter diagnostic devices can simplify cardiometabolic disease diagnosis. Existing devices, however, may not be suitable for use in low-resource settings, where the burden of non-communicable diseases is high. Here, we describe the development of a target product profile (TPP) for a point-of-care multi-parameter device for detection of biomarkers for cardiovascular disease and metabolic disorders, including diabetes, in primary care settings in low- and middle-income countries (LMICs).

Methods:

A draft TPP developed by an expert group was reviewed through an online survey and semistructured expert interviews to identify device characteristics requiring refinement. The draft TPP included 41 device characteristics, each with minimal and optimal requirements; characteristics with an agreement level of ≤85% in the survey or among interviewees were further discussed by the expert group and amended as appropriate.

Results:

Twenty people responded to the online survey and 18 experts participated in the interviews. Twentytwo characteristics had an agreement level of \leq 85% in either the online survey or interviews. The final TPP defines the device, which is intended to be used for basic diagnosis and management of cardiometabolic disorders (measured by lipid, glucose, HbA1c and creatinine levels), as minimal requirement, and offers an expanded test menu for wider cardiometabolic disease management as an optimal requirement. To be suitable, the device should be purposed for level 1 healthcare settings or lower, able to be used by minimally trained healthcare workers, and allow testing using selfcontained cartridges or strips without the need for additional reagents. Throughput should be one sample at a time in a single or multi-analyte cartridge, or optimally enable testing of several samples and analytes in parallel with random access.

Conclusion:

This TPP will inform developers of cardiometabolic multi-parameter devices for LMIC settings and will support decision makers in the evaluation of existing and future devices.

BACKGROUND

Although non-communicable diseases (NCDs) are often thought to be a problem of high-income countries, a large proportion of the burden of NCDs is also borne by low- and middle-income countries (LMICs), with 78% of all NCD-related deaths and 85% of premature NCD-related deaths in people aged between 30 and 69 years occurring in these settings^{1,2}. Cardiovascular diseases (CVDs) and metabolic disorders represent a large proportion of the NCD burden in LMICs^{3,4}, with stroke, ischaemic heart disease, diabetes and chronic kidney disease commonly appearing in the top ten causes of life years lost due to premature mortality⁵. Unlike high-income countries, many LMICs lack the healthcare resources to tackle this increasing burden^{2, 3}. Primary healthcare, with its emphasis on promoting health and preventing disease, is the most effective way to reduce premature mortality from NCDs^{6, 7}, but many primary healthcare facilities in LMICs lack the laboratory capacity needed for diagnosis and monitoring of these conditions⁸. As such, the World Health Organization (WHO) Global Action Plan for NCDs recommends improvement of diagnostic services for the four NCDs with the highest contribution to morbidity and mortality, including CVDs and diabetes, as well as development and equitable dissemination of affordable, effective and quality diagnostics for these diseases⁹.

Prevention, diagnosis and management of CVDs and diabetes is achieved through the monitoring of various laboratory parameters, such as lipids for atherosclerosis, blood glucose for diabetes, serum creatinine for chronic kidney disease, and liver enzymes for liver disease. Based on the results of laboratory tests, best treatment options are chosen, and dosages adapted. Multi-parameter diagnostic devices, which can test for multiple analytes either simultaneously or sequentially from a single sample, hold the potential to streamline and simplify cardiometabolic disease diagnosis and management¹⁰. However, while several multi-parameter devices for CVDs already exist, they may not be suitable for use in LMICs due to resource requirements (e.g. power, storage), the need for trained users, and environmental operating conditions¹¹.

There is a demonstrated need to develop and adopt affordable and effective point-of-care (POC) diagnostic tools that are suitable for use in low-resource primary care settings to improve diagnosis and management of cardiometabolic disease¹². Here, we describe the development of a target product profile (TPP) for a POC multi-parameter device to measure cardiometabolic biomarkers at LMIC primary care. The TPP aims to define the minimal and optimal requirements for a device suitable for use in these settings.

METHODS

The TPP was developed in three stages:

- **1.** Preparation of a draft TPP for diagnosis of cardiometabolic diseases by an expert group;
- **2.** Consensus building through an online survey and expert interviews to identify device characteristics for further refinement;
- **3.** TPP finalization by the expert group.

Draft TPP preparation

Baseline TPP requirements were taken from an earlier TPP (version 0) developed by WHO, FIND, and MSF, which described desired characteristics of a multi-parameter POC polymerase chain reaction (PCR) machine to diagnose infection with pathogens causing febrile illness¹³. Version 0 included 41 characteristics relating to the scope of the device, the instrument, and the assay cartridge, each with minimal and optimal requirements. Version 0 had been fully vetted using a Delphi-like process, involving a stakeholder survey of 52 experts, followed by a TPP working group discussion to address characteristics with low agreement; the process was then repeated, and the revised draft was put forward for a month of public consultation on the WHO and FIND websites.

For the cardiometabolic device TPP development, an expert group was convened to adapt the previously developed TPP (version 0) to create a draft TPP for diagnosis of cardiometabolic diseases (version 1). Members were selected from healthcare organizations or academic centres with an interest in improving health in low-income settings and represented organizations with relevant expertise in NCDs, diagnostics or laboratory work. Areas of expertise for each participating expert group member are shown in Table 1. The expert group meeting took place on 12 December 2019 in Geneva, Switzerland. During the meeting, version 0 of the TPP was adapted to the context of cardiometabolic non-communicable diseases and their management at the primary healthcare level, resulting in amendments to the intended use and target use setting characteristics. Device and assay cartridge configurations were also adapted to reflect the detection of biochemical parameters, rather than the PCR nucleic acid amplification techniques used for infectious disease. This included revisions to characteristics relating to device design, type of parameters, technical aspects for measurement, turnaround times and test results. List prices were also adjusted.

Table 1. Expert group expertise and experience

EXPERT AFFILIATION	EXPERTISE/ROLE	HIGHEST DEGREE
FIND	Non-communicable diseases Lead	PhD
FIND	Chief Scientific Officer, technical product development	PhD
ICRC	Specialist in general internal medicine,	MD
	humanitarian conflict physician	
LH Consulting	Medical diagnostics business consultant	MBA
LSHTM	Cardiovascular clinical epidemiologist	MD, MSc
MSF	Non-communicable diseases advisor and working group leader,	MPH
	physician and international public health specialist	
MSF	Diagnostics network leader, physician and public health specialist	MD, MSc
MSF	Laboratory advisor	PhD
UNHCR	Senior Public Health Officer, humanitarian physician	MPH
UNIGE/HUG	Lecturer and researcher,	PhD
	public health specialist in NCDs, diabetes, and health systems	
WHO	Medical Officer, Physician and epidemiologist	MD/PhD

FIND, the global alliance for diagnostics; ICRC, International Committee of the Red Cross; LH, Lucy Hattingh; LSHTM, London School of Hygiene & Tropical Medicine; MSF, Médecins Sans Frontières; UNHCR, United Nations High Commissioner for Refugees; UNIGE/ HUG, University of Geneva/Hôpitaux Universitaires Genève; WHO, World Health Organization.

Consensus building:

A two-step method was employed to facilitate consensus building for the TPP. Firstly, the draft TPP (version 1) was reviewed through an online survey. Secondly, semi-structured stakeholder interviews were performed to obtain additional feedback on relevant or controversial areas.

The online survey was created using Alchemer, formerly SurveyGizmo, software. A link to the online survey was posted on the FIND LinkedIn account (>10,000 followers) and Twitter account (>7,000 followers). Members of the expert group also distributed the link amongst their respective networks. The survey was open from 14 February to 30 April 2020. Survey respondents were asked to rate their level of agreement with each of the 41 minimal and 41 optimal requirements in the draft TPP (version 1) using a 5-point Likert scale¹⁴. Percentage agreement was determined by the number of respondents with a 'mostly agree' or 'fully agree' rating (score of 4 or 5), and disagreement with a criterion based on a rating of 'fully disagree', 'mostly disagree' or 'neither agree nor disagree' (scores from 1 to 3), which required a comment from the survey respondent explaining their reasons for disagreement. Respondents could provide additional comments to accompany scores of 4 or 5 if desired, but this was not mandatory.

Clinicians, laboratory experts and procurers of POC cardiometabolic devices were targeted for the semi-structured stakeholder interviews. Eligible participants were those who influence or make key decisions on purchase or use of POC cardiometabolic devices at the primary place of usage, and who self-rate as having at least fair or very familiar knowledge of these devices. An expert search agency was employed to identify eligible respondents using a screening questionnaire, aiming to match the number of interviewees to the number of survey respondents as closely as possible. Interviewees were recruited and interviews were conducted between June and July 2020. Interviews were performed by video call and were aided by a semi-structured discussion guide (Annex 1). Calls were recorded with the respondents' permission and analysis was conducted on artificial intelligence-generated transcripts. Notes were taken wherever permission for recording was not provided. Interviews were performed by two employees of IQVIA Inc. (Durham, NC, USA). The interviewers were experienced in qualitative and quantitative research in the healthcare industry and held social science qualifications (BA in Social Science and MSc in Social Research Methods, respectively). The interviewers did not know any of the persons interviewed prior to this study.

Interviewees were categorized into device users, purchase decision makers or both, depending on their feedback from the screening questionnaire. Interviewees were shown 29 of the 41 device characteristics from version 1 of the TPP, relevant to their area of expertise, and were asked to identify the top ten characteristics they considered most important. The order in which the characteristics were shown was rotated for each interviewee to reduce order bias. Eleven characteristics were not included in the interviews as their requirements were deemed less likely to need adaptation due to the stringent baseline definition (data protection, manufacturing quality, regulatory approval, performance criteria, sample volume, memory). The interviews were qualitative in nature; however, characteristics that were mentioned by more than half of the interviewees were also quantified. Quantitatively rated characteristics were scored as a percentage, with the number of interviewees who identified a characteristic as being important as the denominator and the number who agreed with the minimal or optimal requirement as the numerator. Separate to the TPP development, interviewees were also asked to rank the characteristics in the order of most importance.

TPP finalization

To finalize the TPP, the expert group reconvened to discuss the TPP characteristics with an agreement level of \leq 85% for either the minimal or optimal requirement based on either the survey or the interview results. The virtual meeting took place on 4 September 2020 (two experts were excused). The highest priority characteristics were discussed in detail until agreement was reached, while lower priority characteristics were voted on by the expert group to achieve a consensus. The majority (\geq 50%) of respondents who voted on each characteristic needed to vote in favour of an amendment for it to be made.

Ethics and consent

As this research did not include human or animal subjects, no ethical or licensing committee approvals or informed consent were required. There are no specific regulations or guidelines for the development of TPPs; however, the methodology used in this study was consistent with protocols for previous TPPs developed by FIND and/or WHO.

Online survey and semi-structured interviews

Of the 65 people who accessed the online survey, 20 responded, of whom 13 provided complete responses. Respondents were from 15 countries, and the majority were employees of, or consultants for, non-governmental organizations (n=7) or medical doctors (n=6) (Table 2). For the interviews, eighteen experts agreed to participate. The majority were from South Africa (n=6) and India (n=5), and most were clinical experts (Table 2).

Table 2. Characteristics of online survey respondents and interviewees

CHARACTERISTIC	NUMBER
SURVEY RESPONDENTS (N=20)	
COUNTRY	
Germany	1
India	2
Iraq	2
Italy	2
Switzerland	2
United Kingdom	2
Canada	1
Egypt	1
Lebanon	1
Malawi	1
Netherlands	1
Nigeria	1
Uganda	1
Ukraine	1
United States	1
PROFESSION	
Employee/consultant for NGO*	7
Medical doctor	6
IVD diagnostics industry personnel	1
Biomedical Engineer	1
Consultant	1
Epidemiologist	1
Laboratory expert	1
Nurse	1
Public Health	1

CHARACTERISTIC	NUMBER
INTERVIEWEES (N=18)	
COUNTRY	
South Africa	6
India	5
Peru	2
Uganda	2
Bangladesh	1
Brazil	1
Tanzania	1
PRIMARY ROLE	
Clinical	12
Laboratory	4
Procurement	2

*National or international. IVD, in vitro diagnostics; NGO, non-governmental organization

Results from the survey and interviews are shown in Figure 1. In the online survey, of the 41 minimal requirements, 14 had an agreement level of \leq 85%. Minimal requirements with the lowest agreement were list price of the device (70%), weight of the device (71%), and distribution territory (75%). Of the 41 optimal requirements, 12 had an agreement level of \leq 85%. Optimal requirements with the lowest agreement were device memory (64%), target use setting (69%), target user (71%) and training time needed (71%). In the interviews, minimal requirements with a quantitative assessment that had an agreement level of \leq 85% were service, maintenance and calibration (43%), list price of the device (45%) and multiplexing of simultaneous tests (57%). Optimal requirements with a quantitative assessment that had an agreement level of \leq 85% were target user (82%), training time needed (82%), result output (83%), and specimen type (63%). Only two characteristics that had an agreement level of >85% for either requirement in the online survey had an agreement level of \leq 85% in the interviews - multiplexing of simultaneous tests and specimen type.

Figure 1. Results from the online survey and semi-structured interviews

		ONLINE SURVEY INTERVIEWS							
SECTION	CHARACTERISTIC	% AGREEMENT % AGREEMENT WITH MIN N % AGREEMENT WITH OPT						% AGREEMENT	
		MIN	OPT	100% 75% 50% 25% 0%	6	100% 75% 50% 25% 0	%	MIN OPT	
Scope	Intended use	90%	89%	90%	20	89%	19	qualitative	
General	Description of the system	87%	75%	87%	15	75%	16	qualitative	
	Target use setting	94%	69%	94%	17	69%	16	qualitative	
	Target user			79%	14	71%	14	100% 82%	1
Device	Device design	77%	85%	77%	13	85%	13	100% 100%	5 9
	Size	92%	77%	92%	13	77%	13	100% 100%	5 9
	Weight	71%	86%	71%	14	86%	14	100% 100%	5 9
	Power requirements	85%	92%	85%	13	92%	13	100% 100%	5 7
	Throughput	83%	92%	83%	12	92%	13	qualitative	
	Environmental stability; operating range	83%	92%	83%	12	92%	12	100% 100%	5 13
	Biosafety	100%	100%	100%	12	100%	12		
	Training time needed		71%	79%	14	71%	14	100% 82%	11
	Service, maintenance and cali- bration		100%	78%	9	100%	10	43% 93%	14
	Patient identification capability	100%	91%	100%	12	91%	11	100% 100%	8
	Result output	90%	78%	90%	10	78%	9	100% 83%	13
	Data display	100%	92%	100%	13	92%	12	100% 100%	5 9
	Connectivity	92%	92%	92%	13	92%	13		
	Data export and protection	100%	88%	100%	11	88%	8	qualitative	
	Memory	82%	64%	82%	11	64%	11		
	Manufacturing	100%	100%	100%	10	100%	10		
	List price of the device	70%	100%	70%	10	100%	10	45% 100%	5 11
	Device Regulatory Status	89%	100%	89%	9	100%	10		
	Analytes/test menu	89%	78%	89%	9	78%	9	qualitative	
Test	Description of test cartridge / strip	100%	91%	100%	11	91%	11		
Car- tridge/	Multiplexing of simultaneous tests	90%	90%	90%	10	90%	10	57% 86%	7
strips	Additional third party consumables	82%	100%	82%	11	100%	12		
	Specimen type	92%	92%	92%	13	92%	13	100% 63%	8
	Sample volume	91%	91%	91%	11	<mark>91%</mark>	11		
	Limit of detection			78%	9	78%	9		
	Interfering substances	83%	83%	93%	6	83%	6	-	
	Standardization and traceability	100%	100%	100%	10	100%	10		
	Test result	92%	91%	92%	12	91%	11	-	
	Controls	89%	78%	89%	9	78%	9		
	Environmental Stability: transport	92%	92%	92%	13	92%	12		
	Environmental Stability: reagent shelf life	91%	90%	91%	11	90%	10	qualitative	
	Environmental Stability: operating range	91%	91%	91%	12	91%	12	100% 100%	5 1:
	Waste/disposal requirements	100%	100%	100%	9	100%	8		
	Manufacturing	100%	100%	100%	10	100%	10	1	
	Reagent regulatory status	100%	100%	100%	10	100%	10	1	
	List price of assay cartridge/strips	90%	100%	90%	10	100%	10	100% 100%	5 1
	Distribution territory	75%	92%	75%	12	92%	12		
Average		89%	89%	89%		89%		91% 93%	

TPP finalization

In addition to the 22 characteristics with low disagreement in the survey and interviews, the intended use characteristic was also discussed during the expert meeting. While there was a high level of agreement on this characteristic among the survey respondents and interviewees, the intended use is directly linked to the test menu, where agreement was lower. Moreover, survey respondents made a range of comments on this question, so the experts felt it necessary to revisit discussions to confirm the existing description was appropriate. The intended use characteristic was modified to clarify that the scope of the TPP includes management of people with high cardiovascular risk, as well as diagnosis and management of people with cardiometabolic disorders.

While some survey respondents and interviewees disagreed with the optimal target use setting requirement—level 0 health facility without equipped laboratory; electricity with frequent surges and/ or outages; no climate control; dusty environment; mobile testing facilities and medical staff onsite— experts decided to keep this wording, since optimal requirements always define an ideal device. The minimal target user characteristic was reworded to clarify that while general laboratory training was not essential for users of the POC device, specific training for the multi-parameter device would need to be provided; for the optimal requirement, users should be capable of applying this device training. This characteristic was renamed 'target operator'.

In version 1 of the TPP, the minimal requirement for the device design characteristic allowed for the test menu to be covered by multiple instruments. However, the survey respondents felt that this may not be cost effective and would introduce redundancy. The expert group therefore amended the minimal requirement to require a single device to cover the minimal test menu, and the possibility for several devices to be connected to run the same tests in parallel was moved to the optimal requirement. Additionally, based on survey feedback that hand-held devices have limited added value over small tabletop devices for use in primary care settings, and may not be preferred due to greater potential for hand-held devices to be lost, dropped, or misplaced, the optimal requirement for the size of the device was amended to require the device to be portable rather than hand-held. Weight requirements were also amended from ≤ 15 kg to ≤ 10 kg for the table-top device (minimal) and from ≤ 1 kg to and ≤ 2 kg for the portable device (optimal).

Survey respondents were concerned that operational characteristics of the device were not sufficient for countries in which the average summer temperatures are higher than 35°C. The temperature ranges were subsequently increased; a requirement for the device to be water splash proof was also added. Survey respondents and interviewees felt that the training times for users in both the minimal and optimal requirements were too optimistic; however, they believed that this had been interpreted in the context of patient management rather than device operation, and so the wording 'to operate the device' was added to both requirements. Based on interviewee feedback, minimal maintenance requirements were changed from daily to weekly. Survey respondents commented that regional variation in result output should be discouraged; this was therefore removed from the optimal requirement.

There was considerable feedback from survey respondents and interviewees regarding the list price of the device, with many commenting that the minimal cost of 5,000 USD would be an extremely high capital investment for LMIC healthcare centres. Finding the optimal trade-off point between affordability and device sophistication is challenging. However, recurrent costs of the tests may be more important than device cost, as diagnostic devices are often provided free of charge or for a

small service charge on condition that a minimum number of tests are purchased within a defined time period. After much debate, the minimal requirement for list price of the device was lowered to 1,500 USD, noting that a higher price might be acceptable under specific circumstances, such as reagent lease or rental agreements.

With regards to the test menu characteristic (#23), respondents thought the minimal test menu should include explicit result outputs for total cholesterol (TC) and high-density lipoprotein (HDL) to calculate low-density lipoprotein (LDL), rather than limiting the output to calculated LDL, without a specific result output for TC and HDL to the user. The minimal requirement was adapted accordingly. Survey respondents commented that troponin may not be a relevant parameter for settings of intended use of the device; however, it was decided to keep this parameter for optimal requirement so as not to exclude a use case for the device, even if unlikely. Interviewees thought that testing of one analyte at a time would be too time consuming yet noted that the device should allow use of single cartridges to permit individual tests to be conducted at different frequencies and to prevent waste. The minimal requirement for multiplexing of simultaneous tests was therefore changed to 'Testing of one analyte at a time in single or multi-analyte panel cartridge'. Some respondents commented that more interfering substances should be included, so both requirements were amended to state that interference testing should follow Clinical and Laboratory Standards Institute (CSLI) EP37 guidance on substances and threshold levels¹⁵, as these are internationally recognized standards.

It was noted that different analytes may require different sample types, thus the minimal requirement for fingerstick whole blood may be too restrictive. To allow more flexibility around specimen types, the minimal requirement was amended to allow for use of plasma, serum, or urine samples in addition to whole blood, with a limitation of one specimen type per cartridge or strip. The optimal requirement was amended to allow for different specimen types per cartridge or strip. The sample volume requirement was subsequently changed to prescribe a specific volume for fingerstick whole blood only, as this is the most difficult specimen type for which to collect sufficient volume.

Following feedback from online survey respondents that the test should not be limited to certain regions, it was agreed to change the minimal requirement for distribution territory to 'worldwide', and the optimal requirement to 'same as minimal'.

Other minor amendments included renaming of the 'limit of detection' and 'description of the system' characteristics to 'accuracy' and 'description of the device', and clarifying that clinical decision-making based on test results should be performed by clinicians/medical staff. Overall, minimal and/ or optimal requirements were adjusted for 18 of the 23 characteristics discussed. The final TPP is shown in Table 3.

#	CHARACTERISTIC	MIN/OPT	REQUIREMENTS
GEN	ERAL		
1	1 Intended use	Minimal	Intended for basic screening, diagnosis and management of cardiometabolic disorders (e.g. hyperlipidaemia, diabetes and renal function) and also managing people at high cardiovascular risk; excluding neonates
1a		Optimal	Same as minimal, plus offering an expanded test menu to address a wider range of cardiometabolic disorders (e.g. liver function, acute cardiac care); including neonates

 Table 3. Finalized TPP for a multi-parameter cardiometabolic POC device

#	CHARACTERISTIC	MIN/OPT	REQUIREMENTS
GEN	ERAL		
2	Description of device	Minimal	Benchtop (or hand-held) instrument designed for use in combination with self-contained, disposable assay cartridge(s) or strips containing all required reagents to execute a test from sample to result
2a		Optimal	Same as minimal
3	Target use setting	Minimal	Level 1 healthcare facility (primary care) defined as having a rudimentary equipped laboratory, water, electricity with intermittent surges and/or outages, limited climate control, dusty environment; medical staff onsite
За	- Target use setting	Optimal	Level 0 healthcare facility without equipped laboratory, electricity with frequent surges and/or outages, no climate control, dusty environment; includes mobile testing facilities; medical staff onsite
4	Targat aparatar	Minimal	Minimally skilled healthcare worker, e.g. with basic laboratory training (device-specific training provided)
4a	- Target operator	Optimal	Healthcare worker without specific laboratory training, capable of applying device-specific training
DEV	ICE		
5		Minimal	Device with single port capable of interfacing with one cartridge design or strip
5a	Device design	Optimal	Device with several ports capable of interfacing with one or more cartridge designs or strips for simultaneous, independent detection of multiple analytes; possibility for modular connectivity of several devices
6	Ciac	Minimal	Small, table-top device (no larger than 50x70x50 cm)
6a	Size	Optimal	Smaller than minimal and portable
7	M/sistet	Minimal	≤10 kg
7a	Weight	Optimal	≤2 kg
8	Power	Minimal	Local 110–220 V AC mains power, plus uninterruptible power supply (UPS) to complete current cycle; UPS and circuit protector must be integrated within the system
8a	requirements	Optimal	Same as minimal, with rechargeable battery back-up (8-hour operation) or single-use battery (for hand-held)
9	Throughput	Minimal	Throughput processing of one sample at a time; minimum of 10 samples per hour when individual analytes are tested or 4 samples per hour when analyte panels are tested
9a		Optimal	More than one sample at a time with random access and the ability to test different analytes simultaneously
10	Environmental Stability: operating	Minimal	Operation at 10–40°C and up to 90% non-condensing humidity at an altitude up to 2,500 meters; able to function in direct sunlight; able to withstand dusty conditions; water splash proof
10a	range of the device	Optimal	Operation at 5–45°C and up to 98% non-condensing humidity at an altitude up to 3,000 meters; able to function in direct sunlight; able to withstand dusty conditions; water splash proof
11	Biosafety	Minimal	Closed, self-contained system with unprocessed sample transfer; easy decontamination of instrument surfaces
11a		Optimal	Same as minimal
12	Training time	Minimal	Below 1 day for a healthcare worker to operate the device
12a	Training time needed	Optimal	Below 2 hours for a healthcare worker without basic laboratory training to operate the device

#	CHARACTERISTIC	MIN/OPT	REQUIREMENTS					
DEV	CE							
13	Service,	Minimal	Weekly maintenance (<30 minutes, with hands on time <10 minutes); mean time between failures of at least 24 months or 10,000 tests; self-check alerting operator to instrument errors or warnings; operator calibration per new lot or at set time intervals					
13a	maintenance, and calibration 3a	Optimal	Weekly maintenance (<30 minutes, with hands on time <10 minutes); mean time between failures of at least 36 months or 30,000 tests; self-check alerting operator to instrument errors or warnings; ability to be calibrated remotely or no calibration needed (factory calibrated)					
14	Patient	Minimal	Manual entry of alphanumeric patient identifier via keypad, touchscreen or connected result management device (e.g. smartphone)					
14a	identification capability	Optimal	Same as minimal, plus bar code, radio frequency identification (RFID) or other reader					
15		Minimal	Quantitative based on the analytes of detection; qualitative where this is sufficient to inform clinical decision-making					
15a	Result output	Optimal	Quantitative plus option of qualitative readout where that result is sufficient to inform clinical decision-making; ability to select which test results are reported to the user					
16	Data display	Minimal	On-device visual readout with ability to function in various lighting conditions ranging from bright to low ambient light conditions; ability to add information (patient ID, operator ID, date, location, etc.)					
16a		Optimal	Same as minimal, with option to add custom result ranges and alerts to support clinical decision-making by medical staff					
17	Connectivity	Minimal	Ability to connect to a mobile network, or Wi-Fi or use a USB for data transfer					
17a		Optimal	Same as minimal, including Bluetooth and bi-directional communication					
18	Data export and	Minimal	Secured data export with end-to-end encryption connectivity to external printer; passcode-protected machine access					
18a	protection	Optimal	Same as minimal, plus scheduled/automatic data export using interoperable standards; support of any or all of the following formats: HL7, FHIR, ASTM, JSON; passcode-protected individual user access					
19		Minimal	500 patient results, 100 quality control (QC) results					
19a	Memory	Optimal	10,000 patient results, 20,000 QC results or unlimited data storage (cloud-based)					
20	Manufacturing	Minimal	International Organization for Standardization (ISO) 13485:2016 compliant					
20a	Ivialiulacturing	Optimal	Same as minimal					
21	List price of the	Minimal	≤1,500 USD					
21a	device	Optimal	≤300 USD					
22	Device regulatory	Minimal	Approval through at least one Stringent Regulatory Authority (<u>http://www.stoptb.org/assets/documents/gdf/drugsupply/List_of_Countries_SRA.pdf</u>)					
22a	status	Optimal	Same as minimal plus CLIA-waived; WHO-PQ approval if requirements are in place					
TEST	TEST CARTRIDGE/STRIP							
23		Minimal	Glucose, HbA1c, lipids (total cholesterol and HDL to calculate non-HDL cholesterol), creatinine					
23a	Analytes/test menu	Optimal	Same as minimal and full lipid profile (values for cholesterol, HDL, LDL, and triglycerides), liver enzymes (ALT, AST, ALP, GGT, bilirubin), troponin, BNP, ACR, auto calculation of eGFR and others as required for wider cardiometabolic disease management					

#	CHARACTERISTIC	MIN/OPT	REQUIREMENTS
TEST	CARTRIDGE/STRIP		
24	Description of test	Minimal	Self-contained, disposable cartridge(s)/strips containing all required reagents, buffers, or other consumables to execute a test from sample to result
24a	cartridge/ strip Optimal		Same as minimal
25		Minimal	Testing of one analyte at a time in single or multi-analyte panel cartridge
25a	Multiplexing of simultaneous tests	Optimal	Testing of several analytes in parallel, either with multi-analyte panel cartridge, or with several cartridge/strip ports; ability to measure analytes individually, as well as part of a panel
26	Additional third-	Minimal	None, except for sample collection
26a	party consumables	Optimal	None; manufacturer-provided kits contain all required items for sample collection and testing
27		Minimal	Ability to accept one specimen type per cartridge/strip (whole blood or plasma or serum or urine, depending on the parameter)
27a	Specimen type	Optimal	Ability to accept different specimen types per cartridge/strip (whole blood, plasma, serum, urine; non-exclusive with exception of parameter dependency on sample type)
28	Sample volume	Minimal	Minimum sample volume required to reach clinically relevant sensitivities for each test; no more than 50 μ l per parameter for fingerstick whole blood (cumulative volume for panel cartridges)
28a		Optimal	Same as minimal
29	Accuracy	Minimal	Equivalent to state-of-the-art reference assays for the same target analytes; where applicable, clinically relevant LODs are to be met; for troponin, rule-out of myocardial infarction according to ACC/AHA guidelines
29a		Optimal	Same as minimal; for troponin: rule-out of myocardial infarction according to ESC 2018 guidelines
30	Interfering	Minimal	Interference testing should follow CLSI EP37 list of recommended substances
30a	substances	Optimal	Same as minimal
31	Standardization and traceability	Minimal	Test should be standardized based on established methods (e.g. isotope dilution mass spectrometry, ID-MS) and traceable to internationally recognized reference materials (where available).
31a		Optimal	Same as minimal
32	Test result	Minimal	Quantitative result based on the analytes of detection. Qualitative result available to clinician where that result is sufficient to inform clinical decision- making
32a		Optimal	Same as minimal
33	Controlo	Minimal	External positive and negative controls to be run with each new lot and every week
33a	- Controls	Optimal	External positive and negative controls to be run with each new lot and every month
34	Environmental stability: transport	Minimal	No cold chain required; should be able to tolerate stress during transport (cycles of temperature of 30 to 50°C) without affecting the labelled expiry date
34a		Optimal	Same as minimal
35	Environmental	Minimal	18 months at 2–35°C (including 3 months at 40°C); 90% relative humidity
35a	Stability: Reagent shelf life	Optimal	24 months at 2–40°C; up to 98% relative humidity

	CHARACTERISTIC	MIN/OPT	REQUIREMENTS				
TEST	TEST CARTRIDGE/STRIP						
36	Environmental	Minimal	10–40°C; 90% relative humidity				
36a	Stability: Operating range	Optimal	5–45°C; 98% relative humidity				
37	Waste/disposal Requirements	Minimal	No components that are classified with a GHS[1] classification – H(2) that would require waste disposal with high temperature incinerator (or more than a De Monfort type incinerator)				
37a		Optimal	Same as minimal				
38	Manufacturing	Minimal	International Organization for Standardization (ISO) 13485:2016 compliant				
38a	Manufacturing	Optimal	Same as minimal				
39	Reagent regulatory	Minimal	Approval through at least one Stringent Regulatory Authority (<u>http://www.</u> stoptb.org/assets/documents/gdf/drugsupply/List_of_Countries_SRA.pdf)				
39a	status	Optimal	Same as minimal plus CLIA-waived; WHO-PQ approval if requirements are in place				
40	List price of assay cartridge/	Minimal	Strips: ≤ 1 \$ (USD); cartridges: ≤ 3 \$ (USD) per analyte (individual or as part of a panel)				
40a	strips	Optimal	Strips: ≤ 0.5 \$ (USD); cartridges: ≤ 1 \$ (USD) per analyte (individual or as part of a panel)				
41	Distribution	Minimal	Worldwide				
41a	territory	Optimal	Same as minimal				

ACC, American College of Cardiology; ACR, albumin-to-creatinine ratio; AHA, American Heart Association; ALT, alanine aminotransferase; ALP, alkaline phosphatase; AST, aspartate aminotransferase; ASTM, American Society for Testing and Materials; BNP, brain natriuretic peptide; CLIA, Clinical laboratory improvement amendments; CSLI, Clinical and Laboratory Standards Institute; ESC, European Society of Cardiology; FHIR, fast healthcare interoperability resources; eGFR, estimated glomerular filtration rate; GGT, gamma-glutamyl transferase; GHS, globally harmonized system of classification and labelling of chemicals; HbA1c, glycated haemoglobin; HDL, high-density lipoprotein; HL7, health level 7; ID, identification; ID-MS, isotope dilution mass spectrometry; ISO, International Organization for Standardization; JSON, JavaScript object notation; LDL, low-density lipoprotein; LOD, limit of detection; RFID, radio frequency identification; QC, quality control; UPS, uninterruptible power supply; USB, Universal Serial Bus; USD, United States dollars; WHO-PQ, World Health Organization prequalification.

Ranking of device characteristics

Device characteristic rankings from interviewees are shown in Figure 2. For interviewees who were clinicians or potential users of the device (n=13), the characteristics most rated as important were accuracy (previously limit of detection), result output and environmental stability – operating range. The characteristics most rated among the top three most important were accuracy, result output and patient identification capability. For interviewees who were purchase decision makers (n=12), the most commonly identified characteristics were accuracy, environmental stability – operating range, service, maintenance and calibration, and list price of the device. These were also the characteristics most commonly ranked in the top three.

19 | Results




Figure 2. Most important device characteristics for: A) clinicians and users (N=13); B) purchase decision makers (N=12)

Number of interviewees describing characteristic in the top 10
Number of interviewees ranking characteristic in the top 3

DISCUSSION

This TPP defines the minimal and optimal requirements for a multi-parameter cardiometabolic POC device to be used in primary care settings in LMICs. The TPP aims to encourage the development of devices for the diagnosis and management of cardiovascular diseases and metabolic disorders, conditions that are becoming an increasing burden in low-resource countries. Additionally, the TPP may be used to assess existing multi-parameter devices to determine how well they meet needs in LMIC settings¹¹. The TPP is intended to be a 'living document', with requirements to be regularly reviewed and adapted to accommodate evolving needs and technologies.

While this TPP will inform developers and manufacturers on the key capabilities of a device for use in LMICs, we acknowledge that there is no 'one size fits all' approach to diagnosis and management of cardiometabolic disease and risk factors in these settings. Regional features, such as target population, availability of trained specialists and on-site expertise, accessibility of related services, and purchase decision-maker requirements, will influence the exact needs of each country. The TPP was designed for primary care settings; however, primary care facilities can vary widely across regions, from basic temporary or mobile facilities in humanitarian settings to permanent centres with access to laboratory facilities, electricity and trained doctors and nurses. The ideal device would be usable across all primary care settings. Nevertheless, in recognition of the challenges involved in developing devices for use in facilities with limited resources, the minimal requirement is for level 1 healthcare facilities.

The test menu was designed to address the key cardiometabolic diseases in LMICs. Glucose and HbA1c testing for diagnosis and management of diabetes, non-HDL cholesterol testing for atherosclerotic conditions, and creatinine for kidney disease were considered the minimal requirements for the device to be of value. Optimally, the device would also allow measurement of liver enzymes, troponin and brain natriuretic peptide for myocardial infarction and heart failure, and glomerular filtration rate for kidney function. Other common cardiometabolic markers were discussed, including urea, albumin, blood ketones and thyroid-stimulating hormone. However, to ensure that the TPP requirements were not overly restrictive, it was decided to limit the optimal requirements to the analytes described above. Indeed, some survey respondents felt that there may already be too many analytes for a POC device.

Feedback from the expert interviews suggests that accuracy of the device will be the primary consideration for both clinicians and procurers. As the results will be used to inform clinical decision-making, incorrect results could lead to adverse patient outcomes, thus quantitively accurate measurements are likely to be non-negotiable requirements. Additionally, both clinicians and purchase decision-makers emphasized the importance of environmental stability, especially for level 0 healthcare settings. Clinicians also rated patient identification capability as highly important to

allow linking of test results with other patient parameters, as well as easy-to-interpret result outputs. Purchase decision makers identified service and maintenance as key characteristics, since less frequent maintenance can lead to cost savings.

The TPP was developed using a robust multi-step process – a standard approach for the generation of such documents¹⁶⁻¹⁸. However, while TPP development commonly includes a second round of online surveying, this was not deemed necessary for this TPP, since the original TPP had already been fully vetted through both a survey and stakeholder interviews, and the first round had generated a strong body of evidence for the NCD-specific characteristics and requirements. Additionally, we used an agreement level of ≤85% to identify requirements for further discussion, which is more stringent than the 75% used in similar TPP development processes¹⁶⁻¹⁸. While a large proportion of survey respondents from the original TPP (version 0) were clinicians or laboratory experts, they were not necessarily the final users of such devices, which is a frequent limitation of TPPs and has the potential to influence requirements. We aimed to mitigate this limitation in the TPP by including interviews with clinicians and laboratory experts with experience in the use of POC cardiometabolic devices. However, we cannot rule out that a degree of influence persisted from the original TPP, as well as from the online survey respondents of this TPP.

Our methodology has some limitations, including the possibility for bias. For example, the sequence in which the characteristics were presented may have led to disproportionate importance being placed on certain requirements, and the representation of the qualifications of the survey respondents may have resulted in responses being over- or under-emphasized. The survey design also had the potential to encourage agreement as to the quickest route to completion. The survey period coincided with the beginning of the COVID-19 pandemic, which is likely partially responsible for the low response rate since those who would have responded under normal circumstances may have had other priorities. Additionally, as a large proportion of FIND's work is related to infectious diseases, it is possible that only a limited number of subscribers to the FIND Twitter and LinkedIn accounts had relevant expertise in NCDs. Finally, the two-step design of the consensus building process allowed for a broad representation across countries and stakeholders; however, there was limited representation from certain high population middle-income countries such as China, and the geographical differences between the survey respondents and interviewees did not allow for confirmation of country-level feedback received at either stage.

CONCLUSION

This TPP will inform developers and manufacturers who are considering the development of a cardiometabolic multi-parameter device for use in LMIC settings and will support decision makers to evaluate existing and future devices with respect to the TPP requirements.

Availability of data and materials

All data generated or analysed during this study are included in this report (along with its supplementary information files), except for the full survey results and interview feedback, which are withheld to protect the privacy of the participants.

Funding

This work was funded by grants from ICRC and SDC. The funding bodies were not involved in the design of the study, in the collection, analysis and interpretation of data, or in the development of this manuscript.

Acknowledgements

The authors express their gratitude to all interviewees and survey respondents and thank Manisha Sabharwal, MSc and Adrianne Andrade, BA, for conducting the expert interviews. We are also grateful to Professor Arnold von Eckardstein and Dr Regula Steiner from the Institute of Clinical Chemistry at the University Hospital Zürich, Switzerland for providing comments to guide adaptation of the TPP requirements to the context of clinical chemistry testing. Medical writing assistance and editorial support, under the direction of the authors, was provided by Rachel Wright, PhD, funded by FIND, according to Good Publication Practice guidelines.

REFERENCES

- 1. Benziger CP, Roth GA, Moran AE: The Global Burden of Disease Study and the Preventable Burden of NCD. Glob Heart 2016, 11(4):393-397.
- 2. World Health Organization (WHO): Noncommunicable diseases: Country profiles 2018 [https://www.who.int/nmh/publications/ncd-profiles-2018/en/] Accessed 18 December 2020.
- 3. Miranda JJ, Barrientos-Gutierrez T, Corvalan C, Hyder AA, Lazo-Porras M, Oni T, Wells JCK: Understanding the rise of cardiometabolic diseases in low- and middle-income countries. Nat Med 2019, 25(11):1667-1679.
- 4. World Health Organization (WHO): Noncommunicable diseases: key facts (<u>https://www.who.int/en/news-room/fact-sheets/detail/noncommunicable-diseases</u>) Accessed 18 September 2020.
- 5. GBD 2015 Mortality and Causes of Death Collaborators: Global, regional, and national life expectancy, all-cause mortality, and cause-specific mortality for 249 causes of death, 1980-2015: a systematic analysis for the Global Burden of Disease Study 2015. Lancet 2016, 388(10053):1459-1544.
- 6. World Health Organization (WHO): Noncommunicable diseases: progress monitor 2020 (<u>https://www.who.int/publications/i/item/ncd-progress-monitor-2020</u>) Accessed 30 October 2020.

- 7. Demaio AR, Kragelund Nielsen K, Pinkowski Tersbol B, Kallestrup P, Meyrowitsch DW: Primary Health Care: a strategic framework for the prevention and control of chronic non-communicable disease. Glob Health Action 2014, 7:24504.
- 8. Leslie HH, Spiegelman D, Zhou X, Kruk ME: Service readiness of health facilities in Bangladesh, Haiti, Kenya, Malawi, Namibia, Nepal, Rwanda, Senegal, Uganda and the United Republic of Tanzania. Bull World Health Organ 2017, 95(11):738-748.
- World Health Organization (WHO): Global Action Plan for the Prevention and Control of NCDs 2013-2020 (<u>https://www.who.int/publications/i/item/9789241506236</u>) Accessed 02 December 2020.
- 10. UNITAID: Multi-disease diagnostic landscape for integrated management of HIV, HCV, TB and other coinfections (<u>https://unitaid.org/assets/multi-disease-diagnostics-landscape-for-integrated-management-of-HIV-HCV-TB-and-other-coinfections-january-2018.pdf</u>) Accessed 18 September 2020.
- 11. Foundation for Innovative New Diagnostics (FIND): Landscape of point-of-care devices for testing of cardiometabolic diseases (<u>https://www.finddx.org/wp-content/uploads/2020/02/Landscape-of-poc-devices-for-cardiometabolic-diseases-28FEB2020.pdf</u>) Accessed 18 September 2020.
- 12. Checkley W, Ghannem H, Irazola V, Kimaiyo S, Levitt NS, Miranda JJ, Niessen L, Prabhakaran D, Rabadan-Diehl C, Ramirez-Zea M et al: Management of NCD in low- and middle-income countries. Glob Heart 2014, 9(4):431-443.
- 13. World Health Organization (WHO): A Multiplex Multi-Analyte Diagnostic Platform [] Accessed 18 September 2020.
- 14. Likert R: A Technique for the Measurement of Attitudes. Archives of Psychology 1932, 140:1-55.
- 15. Clinical and Laboratory Standards Institute (CSLI): EP07 Supplement (EP37): Supplemental Tables for Interference Testing in Clinical Chemistry, 1st Edition (<u>https://clsi.org/standards/products/</u><u>method-evaluation/documents/ep07-supplement/</u>) Accessed 30 October 2020.
- 16. Pelle KG, Rambaud-Althaus C, D'Acremont V, Moran G, Sampath R, Katz Z, Moussy FG, Mehl GL, Dittrich S: Electronic clinical decision support algorithms incorporating point-of-care diagnostic tests in low-resource settings: a target product profile. BMJ Glob Health 2020, 5(2):e002067.
- 17. Ferreyra C, Osborn J, Moussy F, Alirol E, Lahra M, Whiley D, Shafer W, Unemo M, Klausner J, Kelly Cirino C et al: Developing target product profiles for Neisseria gonorrhoeae diagnostics in the context of antimicrobial resistance: An expert consensus. PLoS One 2020, 15(9):e0237424.
- 18. Kadam R, White W, Banks N, Katz Z, Dittrich S, Kelly-Cirino C: Target Product Profile for a mobile app to read rapid diagnostic tests to strengthen infectious disease surveillance. PLoS One 2020, 15(1):e0228311.

ANNEX 1 SEMI-STRUCTURED DISCUSSION GUIDE

I have here a set of characteristics or attributes that are typically considered when it comes to POC cardiometabolic devices.

1. (MODERATOR EXPOSES/READS OUT LIST OF ATTRIBUTES) Please have a look at this and identify the TEN most important attributes

(NOTE: MODERATOR WILL EXPOSE EACH TPP CHARACTERISTIC AS TEXT IN A SCREENSHARED WHITEBOARD FACILITATED BY MODERATOR ON WEB-BASED PLATFORM. MODERATOR WILL ENSURE THE ORDER OF EXPOSURE WILL BE ROTATED PER RESPONDENT TO MANAGE ORDER BIAS. RESPONDENT WILL SEE/ HEAR ONLY THE VALUES UNDER THE (TPPs) COLUMN. THE FOLLOWING TPP CHARACTERISTICS FROM THE DRAFT TPP (VERSION 1) WILL BE SHOWN, WITH MINIMAL AND OPTIMAL REQUIREMENTS. CHARACTERISTICS WILL BE EXPOSED ACCORDING TO RESPONDENT TYPE: U – ONLY Users, PDM – ONLY Purchase Decision Makers, UPDM – BOTH Users and Purchase Decision Makers)

- Intended use (UPDM)
- Description of the system (UPDM)
- Target use setting (UPDM)
- Target user (UPDM)
- Device design (UPDM)
- Size (U)
- Weight (U)
- Power requirements (UPDM)
- Throughput (PDM)
- Environmental stability: operating range of the device (U)
- Biosafety (UPDM)
- Training time needed (UPDM)

- Service, maintenance, and calibration (U)
- Patient identification capability (U)
- Result output (U)
- Data display (U)
- Connectivity (UPDM)
- List price of the device (PDM)
- Analytes/test menu (U)
- Description of test cartridge/strip (U)
- Multiplexing of simultaneous tests (UPDM)
- Additional third-party consumables (PDM)
- Specimen type (U)
- Test result (U)
- Controls (UPDM)
- Environmental stability: transport (PDM)
- Environmental stability: reagent shelf life (UPDM)
- Environmental stability: operating range (UPDM)
- List price of assay cartridge/strips (PDM)

2. Looking at these 10 that you have selected, now please rank them from 1-10, starting with 1 being the most important.

3. For each rank that you have provided – please suggest what should be the most optimal and minimal level of capability for each characteristic. (Moderators to probe on TPP phrasing).

